



CRN TOC Waiver

TOC Reference Number: CRN 17-066 Expiry Date: 25 March 2018 or until published

Distributed to: **CRN Train Control**

CRN Website

Issued by: Bryan Turnbull

Requested by: Principal Engineer Rolling Stock & Plant

Issued Date: 25 September 2017 Start Date: 25 September 2017

Subject: Update of West Sections 1 and 2-Speed of Locos and Rolling Stock

This is a waiver to the published rolling stock operating conditions specified in the West Section Pages- Sections 1 and 2, of the CRN Train Operating Conditions Manual. With reference to the attached Tables the following highlighted amendments have been made

West Section Pages -Section 1 - Bowenfels to Parkes

1. Sections 1C & 1D: Locomotive S rating increased from S4 to S3.

West Section Pages -Section 2 - Orange to Dubbo

1. Section 2A - Locomotive S rating increased from S4 to S3

Bryan Turnbull Signature: Phone: (02) 9872 1713 Authorised by: Bryan Turnbull (02) 9872 1713 Fax: Position Title Principal Engineer Rolling Stock and Plant 0407 234 480 Mobile:


> John Holland Rail Email: bryan.turnbull@jhg.com.au

Bowenfels - Orange - Parkes

1

SECTION 1A	Bowenfels - Orange East Fork Junction										
	Vehicle Type		Freight Axle Load/Speed								
	venicle Type	19t	19.5t	20t	20.25t	21t	21.75t	23t	25t		
Freight	Α	115	115	100 (h)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	В	100	100	100 (h)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	С	80	80 (e)	80 (e)	80	80	80 (j)	80	80 (k)		
	D	65									
	E	115	115	80 (g)	80 (g)						
	F								65 80 (k)		
	Load Rating	S3 to S6		S7	S8 to S10		S11	S12 to S13			
Locomotives	Max Axle Load	22.3t		20t	18.7t		15.9t	17.3t			
Locomotives	Max Speed	1	15	90	115		80	100			
	Multiple Locos		4	4	4		4	4			
Passenger	XPT	160									
	Xplorer	145									
	Other	115									

SECTION	Orange East Fork Junction - Parkes										
1B	Validate Toma	Freight Axle Load/Speed									
10	Vehicle Type	19t	19.5t	20t	20.25t	21t	21.75t	23t	25t		
Freight	А	115	115	100 (h)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	В	100	100	100 (h)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	С	80	80 (e)	80 (e)	80	80	80 (j)	80	80 (k)		
	D	65									
	E	115	115	80 (g)	80 (g)						
	F								65 80 (k)		
	Axle Rating	S3 to S6		57	S8 to S10		S11	S12 to S13			
Lacamativas	Max Axle Load	22.3t		20t	18.7t		15.9t	17.3t			
Locomotives	Max Speed	1	15	90	115		80	100			
	Multiple Locos	4		4	4		4	4			
	XPT	160									
Passenger	Xplorer	145									
	Other	115									



Safe Working System

Bowenfels to Orange East Fork Jn - Rail Vehicle Detection Orange East Fork Jn - Orange /Parkes

Train Order Working

Refer to the line diagram for Train Order locations

Refer to Page 2 for Sections 1C, 1D and Notes



SECTION	Orange East Fork Junction - Orange										
10	Vehicle Type	Freight Axle Load/Speed									
10	venicle Type	19t	19.5t	20t	20.25t	21t	21.75t	23t	25t		
	Α	70	70	70	70	70	70	70			
	В	70	70	70	70	70	70	70			
	С	70	70	70	70	70	70	70	70 (k)		
Freight	D	65									
	E	70	70	70 (g)	70 (g)						
	F								65		
	'								80 (k)		
	Axle Rating	S3 to S13									
Locomotives	Max Axle Load	22	2.3t								
(a)	Max Speed	7	70								
	Multiple Locos		4								
	XPT	70									
Passenger	Xplorer	70									
	Other	70									

SECTION 1D		Orange West Fork										
	Vehicle Type	Freight Axle Load/Speed										
		19t	19.5t	20t	20.25t	21t	21.75t	23t	25t			
	Α	70	70	70	70							
	В	70	70	70	70							
Evoluht	С	70	70	70	70							
Freight	D	65										
	E	70	70	70 (g)	70 (g)							
	F											
	Axle Rating	S3 to S13										
Locomotives	Max Axle Load	22.3t										
(a)	Max Speed	70										
190 - 400, 100	Multiple Locos	4										
	XPT	70	0.									
Passenger	Xplorer	70										
	Other	70										

NOTES

- (a) Unless shown otherwise, S2 and S3 locomotives are not permitted to operate on this corridor except when configured as an S5 locomotive, by short loading of fuel as required by Note R19 in Section 10 of the TOC Manual.
- (e) Only vehicles covered by Note R1 in Section 10 of the TOC Manual
- (g) Only vehicles covered by Note R16 in Section 10 of the TOC Manual
- (h) Only vehicles covered by Note R20 in Section 10 of the TOC Manual
- (i) Only vehicles covered by Note R5 in Section 10 of the TOC Manual
- (j) Only vehicles covered by Note R4 in Section 10 of the TOC Manual
- (k) 25t axle load permitted on nominated grain wagons and FRAY container wagons


Orange - Dubbo

2

SECTION	Orange - Dubbo										
2A	Vehicle Type	Freight Axle Load/Speed									
20	venicle Type	19t	19.5t	20t	20.25t	21t	21.75t	23t	25t		
Freight	Α	115	115	100 (h) 100 (l)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	В	100	100	100 (h)	100 (h)	100 (h)	80 (i) 80 (j)	80 (i)			
	С	80	80 (e)	80 (e)	80	80	80 (j)	80 (i)	80 (k)		
	D	65									
	E	115	115	80 (g)	80 (g)				į.		
	F								65 80 (k)		
	Load Rating	S3 to S6		S7	S8 to S10		S11	S12 to S13			
Locomotives	Max Axle Load	22.3t		20t	18.7t		15.9t	17.3t			
(a)	Max Speed	115		90	115		80	100			
	Multiple Locos	4		4	4		4	4			
	XPT	160									
Passenger	Xplorer	145									
	Other	115									



- (a) Unless shown otherwise, S2 and S3 locomotives are not permitted to operate on this corridor except when configured as an S5 locomotive, by short loading of fuel as required by Note R19 in Section 10 of the TOC Manual.
- (e) Only vehicles covered by Note R1 in Section 10 of the TOC Manual
- (g) Only vehicles covered by Note R16 in Section 10 of the TOC Manual
- (h) Only vehicles covered by Note R20 in Section 10 of the TOC Manual
- (i) Only vehicles covered by Note R5 in Section 10 of the TOC Manual
- (j) Only vehicles covered by Note R4 in Section 10 of the TOC Manual
- (k) 25t axle load permitted on Nominated grain wagons and FRAY container wagons
- (I) Only vehicles covered by Note R20 in Section 10 of the TOC Manual



Safe Working System

Orange - Dubbo - Train Order Working

Refer to the line diagram for Train Order locations