

Using brakes

Purpose

To prescribe the rules for using train brakes safely in the Country Regional Network (CRN).

Using airbrakes

Holding trains on grades

Trains that come to a stand on grades must be held stationary in accordance with the requirements specified in the JHR Train Operating Conditions (TOC) manual.

Light trains on grades

Single or multiple light locomotives, and trains hauled by locomotives whose total weight is greater than the net train weight, must descend grades in accordance with the requirements specified in the TOC manual.

Multiple power units

If there are additional motive power units in a train, the Driver in the leading locomotive must:

- have control of the airbrake throughout the train, and
- direct additional Rail Traffic Crew to apply or reduce power as required.

Effective communication must be maintained between the Driver in the leading locomotive and additional Rail Traffic Crew.

The Driver in the leading locomotive of an assisted train does not need to control the airbrake of an assisting bank locomotive.

Abnormal or defective airbrake application

If, during travel, there is abnormal application of airbrakes or the braking performance is inadequate, the Rail Traffic Crew must:

- bring the train to a complete stop, and
- follow the requirements of Rule CNTR 400 Protecting rail traffic, and
- if possible, determine the cause of the application or the extent of the defect, and
- if possible, remedy the cause or defect, and
- tell the Network Control Officer if the defect cannot be remedied.

Airbrake cut-outs

If a train with defective airbrakes travels with airbrake cut-outs, it may be operated only in accordance with the requirements specified in the TOC manual.

Using brakes

Detaching and attaching locomotives

Before detaching a locomotive from a train, the Rail Traffic Crew must secure the train against movement in accordance with the requirements specified in the TOC manual.

After attaching a locomotive to a stationary train, the Rail Traffic Crew must fully pressurise the brake pipe before releasing handbrakes.

Defective handbrakes

If handbrakes cannot be applied, or if handbrakes are suspected or reported to be applied during travel, the Rail Traffic Crew must, if possible:

- determine the cause of the defect, and
- remedy the defect, and
- if the defect cannot be remedied, tell the Network Control Officer.

If a vehicle with non-operating handbrakes is to travel, adjoining vehicles in the train consist must, unless it is specially authorised otherwise, have operational handbrakes.

Re-marshalling

A vehicle with handbrakes that cannot be applied must not be marshalled:

- as the last vehicle of a passenger train, or
- as one of the last three vehicles of a freight train, or
- adjoining other vehicles with handbrakes that cannot be applied.

Labelling vehicles

If defective handbrakes of vehicles cannot be remedied during the journey, the vehicles must be clearly labelled NO HANDBRAKE on both sides.

Stabling detached vehicles

To stable a detached vehicle without working handbrakes, it must be coupled to a vehicle that:

- has working handbrakes, and
- can secure the combined weight of both vehicles.

JHR Network Procedures

Nil

Effective date

October 2019